


1) Kühlwasseranschluss  $\phi$  9.5 (optional)  
cooling water connection  $\phi$  9.5 (optional)

VARIVENT® In-line Gehäuse (optional)  
VARIVENT® In-line access unit (optional)

Nennweite Nominal Size	$\phi$ A	B	C	D
DN40	38	180	60	510.5
DN50	50	180	72	522.5
DN65	66	250	88	538.5
DN80	81	250	103	553.5
DN100	100	250	122	572.5
DN125	125	250	147	597.5
DN150	150	300	172	622.5
1 1/2" OD	34.9	180	57	507.5
2" OD	47.6	180	69.5	520
2 1/2" OD	60.3	250	82	532.5
3" OD	73	250	95	545.5
4" OD	97.4	250	119.5	570
2" IPS	56.3	228.6	79	529.5
3" IPS	84.3	304.8	107	557.5
4" IPS	109.7	304.8	132	582.5
6" IPS	162.7	304.8	184	634.5

<b>Massblatt</b> <b>ColorPlus 2 in-line</b> <b>plan</b>	<b>Massstab</b>  <b>1:1.5</b>	Datum	10.07.2014
		Geprüft	Phs
		Verteiler	
		Gezeichnet	Phs
 <b>SIGRIST</b>		© SIGRIST-PHOTOMETER AG CH-6373 Ennetbürgen www.photometer.com	
PROCESS-PHOTOMETER Technische Änderungen vorbehalten. Subject to change without notice.		<b>Zeichnungs-Nr.</b> <b>COLORPLUS2-MB</b>	
		<b>Index</b> <b>2</b>	