

TurBiScat 2 Ex

Turbidimeter with VARINLINE Connection



Applications

- Filtration monitoring and control
- Turbidity in whisky (cold filtration)
- Turbidity in alcohol in general

Industries

- Beverage
- Food
- For other industries see TurBiScat 2 Ex with flange connection

Advantages

- Two-angle measurement with one measuring head
- Optional colour measurement at 430 nm
- Integrated measured value display and communication modules
- Simple operation through WLAN-capable devices
- Protection class Zone 1, Ex db IIC T3/T4/T5/T6 Ga/Gb
- Measuring range 0 ... 4'000 NTU
- Sealless design
- Easy installation on standard in-line enclosures
- Hygienic design
- Dual beam measurement to compensate for colour and window contamination
- Simple adjustment with calibration unit
- Sensor check function

TurBiScat 2 Ex

Turbidimeter with VARINLINE Connection

Innovations with tangible benefits



Convincing Design

Combination of Hastelloy® and sapphire in a compact, sealless design with LED technology:

- Simple installation
- Allows operation in practically all process applications.
- Minimal maintenance and servicing work



Highest Precision, Large Measuring Span

Highest quality components and precise workmanship result in a high measuring span. An optional integrated colour measurement is available:

- One sensor type for numerous applications.
- Precise measurement of lowest up to very high turbidity values.
- Colour measurement in the same sensor



Integrated Operation and Communication

- Display for measured values and status
- Visualisation of measurement data over the last 7 days
- Proximity sensor for operation
- Configuration via WLAN and integrated web server
- Various communication modules



Monitored Reliability

Formazin is used in the factory to calibrate the TurBiScat 2 Ex after assembly. For QC purpose and possible recalibration, a secondary solid reference standard is available.

- Precise verification and recalibration without the use of Formazin.
- The integrated sensor check periodically checks the function of the light receivers and amplifiers:
- Ensures reliable measurement

Technical Data

Sensor:

Measuring principle:

90° / 25° scattered light at 650 nm (optional colour measurement at 430 nm)

Conformities:

Ex-protection type/
Temperature class:

Ex db IIC T3/T4/T5/T6 Ga/Gb, temperature class depending on medium temperature:

Medium temperature	Temperature class
-20 ... +80 °C	T6
-20 ... +95 °C	T5
-20 ... +130 °C	T4
-20 ... +180 °C	T3

Wavelength turbidity:

LED 650 nm

Wavelength colour (optional):

LED 430 nm

Measuring span turbidity:

0 ... 4'000 NTU

Measuring ranges:

8, freely programmable

Resolution:

0.001 NTU

Measuring span colour:

0 ... 200 E/m

Installation:

In-line housing VARINLINE® or compatible

Material sensor head:

Hastelloy® C-22

Material housing:

Stainless Steel 1.4462/ 1.4404/
Borosilicate glass

Windows:

Sapphire

Sample temperature:

-20 ... +180 °C, depending on the medium and ambient temperature, optional cooling is required.

Max. pressure:

2 MPa (20 bar)

Ambient temperature:

-20 ... +60 °C

Ambient humidity:

0 ... 100 % rel. humidity

Operating voltage:

24 VDC ± 10 %

Protection degree:

IP66

Display:

Colour graphic

Operation:

Proximity sensor

WLAN module:

WLAN according to IEEE 802.11 b/g/n

Communication modules:

6 configurable inputs/outputs
- outputs: 0/4 ... 20mA, digital
- inputs: digital

In preparation:

- Ethernet with POE:
10/100BaseT Ethernet with web server and Modbus-TCP
- Profibus DP
- Profinet IO

External control unit:

Optional (without ex- protection)



photometer.com/ts2e

Applied Process Technology

Galileilaan 33J | 6716 BP Ede
Postbus 234 | 6710 BE Ede
T. +31 88 278 28 28
info@apt.nl | www.apt.nl

SIGRIST
PROCESS-PHOTOMETER
SIGRIST-PHOTOMETER AG
Hofurlistrasse 1 · CH-6373 Ennetbürgen
Tel. +41 41 624 54 54 · Fax +41 41 624 54 55
www.photometer.com · info@photometer.com