



| Nennweite<br>Nominal size | Ø A   | B     | C     | D     |
|---------------------------|-------|-------|-------|-------|
| DN40                      | 38    | 180   | 30    | 36    |
| DN50                      | 50    | 180   | 36    | 42    |
| DN65                      | 66    | 250   | 44    | 50    |
| DN80                      | 81    | 250   | 51.5  | 57.5  |
| DN100                     | 100   | 250   | 61    | 67    |
| DN125                     | 125   | 250   | 73.5  | 79.5  |
| DN150                     | 150   | 300   | 86    | 92    |
| 1 1/2" OD                 | 34.9  | 180   | 28.5  | 34.5  |
| 2" OD                     | 47.6  | 180   | 34.75 | 40.75 |
| 2 1/2" OD                 | 60.3  | 250   | 41    | 47    |
| 3" OD                     | 73    | 250   | 47.5  | 53.5  |
| 4" OD                     | 97.4  | 250   | 59.75 | 65.75 |
| 2" IPS                    | 56.3  | 228.6 | 39.5  | 45.5  |
| 3" IPS                    | 84.3  | 304.8 | 53.5  | 59.5  |
| 4" IPS                    | 109.7 | 304.8 | 66    | 72    |
| 6" IPS                    | 162.7 | 304.8 | 92    | 98    |

PhaseGuard HT Standard:  $\geq$  DN65, 2 1/2" OD, 3" IPS

VARIVENT® In-line Gehäuse (optional)  
VARIVENT® In-line access unit (optional)

Massblatt  
PhaseGuard C / T / HT  
plan

Masstab  
1:1

|            |            |
|------------|------------|
| Datum      | 10.07.2014 |
| Geprüft    | Phs        |
| Verteiler  |            |
| Gezeichnet | Phs        |

**SIGRIST**  
PROCESS-PHOTOMETER

© SIGRIST-PHOTOMETER AG  
CH-6373 Ennetbürgen  
www.photometer.com

Zeichnungs-Nr.  
PhaseGuard-MB

Index

4

Technische Änderungen vorbehalten. Subject to change without notice.